

Product name Innoprep 40

File number 384-040

PRODUCT FAMILY	Adhesion promoter			
DESCRIPTION	Solvent borne adhesion promoter for polypropylene and other low energy substrates.			
INTENDED USES	To be applied under the Uraqua coating system on exterior architectural components			
PRATICAL INFORMATION	Color	transparent		
	Gloss level	N/A		
	Volume solids	9%		
	Film thickness	between 0.2 and 0.5 mils dry (a coat exceeding this limit will not perform well)		
	Viscosity	10 sec Ford cup #4		
	Theoretical coverage	N/A		
	Practical coverage	Consider the appropriate loss factor in accordance with the application equipment and technique.		
	Drying time (75°F 50% relative humidity)	Dry to touch 30 Minutes	Dry to handle 30 Minutes	Hard Dry 30 Minutes
	Overcoating interval with recommended topcoats	Minimum: 30 Minutes		Maximum: 8 Hours
	PRODUCT CHARACTERISTICS	This product allows to reach an excellent adhesion of the subsequent paint coats in dry and wet conditions. It dries quickly and can be topcoated in a short delay.		
SYSTEM'S COMPATIBILITY	This product has been designed to be used under the Uraqua topcoat made for window and door components. It can also be used under the Innocryl coating on polypropylene exterior siding.			
REGULATORY DATA	Flash Point	please refer to the Material safety safety datasheet		
	Product weight	1 litre = 0.87 kg		
	VOC	790 g/l		
APPLICATION DATA	Mixing and Ratio	not applicable		
	Pot life	N/A		
	Airless spray	Recommended		
	Air spray	Recommended		
	Electrostatic application	Not-recommended		
	Other equipment	N/A		
	Thinner	N/A		
	Instructions for shutdowns or longer stops	Flush equipments with lacquer thinner 510-105		

Cleaner Lacquer thinner 510-105, avoid recycled solvents.

Clean up Flush and wash equipment with lacquer thinner 510-105

**SURFACE
PREPARATION**

The surface must be cleaned with either acetone (498-019) or with the Innoprep 056 (498-056). It must be free of dust and any other contaminant such as grease, oil, silicone, etc.

**ADDITIONAL
INFORMATION**

This product is dedicated for an industrial use. Any activity related to the application of this product and waste disposition must be made in accordance with the national rules and regulations in regards to health, safety and environment.

**SAFETY
PRECAUTIONS**

Please, read carefully the Material Safety Data Sheet provided by Société Laurentide Inc. before using this product.

STORAGE

The product is flammable and should be stored away from heat sources. The product sold in cans under pressure, it must be stored away from heat sources.

[Suggérer une modification](#)

Google Traduction pour les entreprises :Google Kit du traducteurGadget TraductionOutil d'aide à l'export

The product is flammable and should be stored away from heat sources. The product sold in spray cans is under pressure, it must be stored away from heat sources.

DISCLAIMER

The above specifications are provided by Société Laurentide Inc. for information purposes only and in no way constitute a representation, promise, or guarantee regarding product use, life cycle or quality. The product identified above must be used in strict conformance with the instructions referred to as well as any other instructions guidelines, or warnings issued by Société Laurentide Inc. Société Laurentide's liability is limited to reimbursement of purchase of a defective product.

LAST UPDATE

2017-07-17
