

# DUROTONE™

INTERIOR  
Latex

Easy to  
apply

Paint Experts'  
Choice

## 291-060 DUROTONE

Interior Acrylic Latex, eggshell finish, low VOCs



Type	Acrylic
Gloss level	8-12 % (60°), 15-25 % (85°)
Finish	Eggshell
Viscosity	95-105 K.U.
Coverage	10 to 14 m <sup>2</sup> /L; (107 to 150 ft <sup>2</sup> /L)
Thinner / cleaner	Water
Format	18.9 L
Drying time	Touch: 30 to 60 minutes <sup>1</sup> Recoat: 2 to 4 hours
Concentration of Solids	By volume: 32 to 38 % By weight: 40 to 48 %
VOCs	< 5 g/l
Colour	<b>291-060</b> Absolute White

### Description

High quality eggshell finish paint with low VOC emissions. It contains no lead or mercury. Superior adhesion. Opaque, non-yellowing, non-spattering and nearly odourless. This paint is ideal for walls with uneven surfaces. It is washable and scrub-resistant as well as mold resistant.

### Coloring

Do not color this product, as this may affect its quality.

### Storage

Store in a dry, well-ventilated place at a moderate temperature (approx. 20°C). Avoid freezing.

### Warning

Keep from freezing.

### Surfaces Preparation

Surface preparation is essential for the final success of the project. All surfaces must be clean, dry and free of contaminants and mould. High gloss surfaces should be sanded to allow for better paint adhesion. Remove old, flaking paint. Thoroughly clean the surface to be painted with a trisodium phosphate solution (TSP). Rinse well.

- **Bare wood:** Apply a latex anti-bleed primer (pine, spruce, cedar). It is important to seal the knots. Some woods require the use of a product such as Shellac on the knots.
- **New gypsum:** Plaster must be dry and clean before painting. Apply sealer-primer for optimum adhesion.
- **Previously latex-painted surfaces:** Apply a coat of latex primer.
- **Previously alkyd-painted surfaces:** If the existing alkyd coating has a matte finish, apply latex primer, but if the finish is glossy, sand the surface with sandpaper # 120 or # 220 and wash to remove any residue. This will allow the latex primer to adhere
- **New concrete and masonry:** Concrete must be thoroughly dry before painting. Wash with muriatic acid and rinse well with water. Apply a coat of latex primer.
- **Metals:** Prepare the surface with a metal primer, then apply the paint according to the application instructions.

**Consult your municipality for proper disposal of leftover product or the following link: [ecopeinture.ca](http://ecopeinture.ca)**

Before using this product, consult its Material Safety Data Sheet for use of protective equipment (section 8), preventive measures (section 7), emergencies and first aid procedures (section 4). The above data is provided by Laurentide Paint for information purposes only and in no way constitutes a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used strictly in accordance with the specifications mentioned and any other instructions, warnings or directives issued by Laurentide Paint and its parent company Société Laurentide inc.

# Laurentide Paint

## DUROTONE™

INTERIOR  
Latex

Easy to  
apply

Paint Experts'  
Choice

## 291-060 DUROTONE

Interior Acrylic Latex, eggshell finish, low VOCs



### Application

Shake the container well before use. Use a paddle to stir to the bottom of the container. Apply with a synthetic fibre brush (polyester, nylon) and a good quality lint-free roller (10 mm). For application with an airless system use the product as is. Never apply below 10°C and above 32°C. Humidity should be less than 50%. Ventilate the room well. For best product performance, two coats should be applied.

### Application with a spray gun

Each application, such as a primer or topcoat, requires the combined choice of certain components such as the nozzle and application filters. Tools such as nozzles also need to be very clean to ensure flawless results. It is important to dilute the product by 5% to 8% with water to ensure even application.

- Recommended viscosity: Minimum of 75-80 KU
- Instructions for interrupting production: Thoroughly rinse or clean the nozzle and air cap and keep the paint containers closed to avoid skin formation.
- Cleaning product: Hot water if possible, otherwise water only. A cleaning solvent may be used if there is dry paint on the equipment.
- Drying time: Touch dry (2 hours) or through dry (4 hours).

### Conventional spray gun

For uniform paint application, we generally recommend:

- Nozzle of minimum 1.8 to 2.0 mm, 40-45 PSI for supply.

### Air-assisted spray gun

For uniform paint application, we generally recommend:

- Nozzle 0.013 to 0.017, gun pressure 1500 PSI to 2500 PSI.
- Kremlin nozzle: Minimum of 06xx.

### Airless Pump Gun

For uniform paint application, we generally recommend:

- Nozzle 0.013 to 0.017, gun pressure 1500 PSI to 2500 PSI.
- Graco Nozzle: Model RAC X 213 to 617.

### Cleaning of tools

Wash with soapy water.

### Care instructions

It is best to use a soft cloth or sponge and a mild household soap. Do not use abrasive cleaners. Rinse off soap residue thoroughly. To allow full performance of this paint, wait at least 3-4 weeks before washing for the first time.

### Limited warranty

The manufacturer guarantees the performance of this product if it is used and applied in accordance with the instructions and technical information. No other form of guarantee is given as there is no control over the application procedures and conditions or the circumstances of use. This limited warranty is non-transferable and does not cover handling charges and manpower costs incurred.

**Note:** Do not use this paint to paint the floor.

- 1 Drying can take longer in cold and humid conditions.

For any other information, contact our customer service department from 8 a.m. to 4:30 p.m. Monday to Friday at the following toll-free number: 1 800 567-9481. You can also reach us by e-mail at [info@peinturelaurentide.com](mailto:info@peinturelaurentide.com) or visit our website at [peinturelaurentide.com](http://peinturelaurentide.com) for more information.

Before using this product, consult its Material Safety Data Sheet for use of protective equipment (section 8), preventive measures (section 7), emergencies and first aid procedures (section 4). The above data is provided by Laurentide Paint for information purposes only and in no way constitutes a representation, promise or warranty as to the use, duration or quality of the product. The identified product must be used strictly in accordance with the specifications mentioned and any other instructions, warnings or directives issued by Laurentide Paint and its parent company Société Laurentide inc.

